

銅製電纜接頭(BCG型)

Metal Cable Gland (TYPE BCG)

SONGYAM



TYPE BCG(A)

TYPE BCG

TYPE BCG-M (銅制電纜接頭)

- 產品材質：採用黃銅加工，表面鍍鎳；TPE塑料，改性橡膠。
- 防護等級：IP68
- 產品性能：固定纜纜，防液體滲漏，耐腐蝕，機械强度高。通過RoHS測試

- Type-SCG
SCG is the connector which is used to secure the cable
- Material: Brass nickel surface,TPE plastics, rubber modified
- Protection Degree: IP66
- Properties: Secure the cable,liquidtight,corrosion resistance,high mechanical strength, passed RoHS

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
BCG-M8	M8×1.0	3-7	6	14
BCG-M10	M10×1.0	3-7	6	14
BCG-M12	M12×1.5	3-7	6	14
BCG-M14	M14×1.5	3-7	6	16
BCG-M16	M16×1.5	4-8、6-10	7	18、20
BCG-M18	M18×1.5	6-10	7	20
BCG-M20	M20×1.5	8-12、4-8、6-10、10-14	8、7、7、7	22、22、22、24
BCG-M22	M22×1.5	10-14、8-12	8、8	24、24
BCG-M24	M24×1.5	10-14	8	27
BCG-M25	M25×1.5	10-14、10-16、13-18	8、8、8	27、28、30
BCG-M27	M27×1.5	13-18、10-16	8	30、30
BCG-M30	M30×1.5	13-18、10-16、15-20	8、8、8	34、34、34
BCG-M32	M32×1.5	15-22、13-18、18-25	9、8、9	34、34、40
BCG-M33	M33×1.5	15-22	9	36
BCG-M36	M36×1.5	18-25、15-22	9	40、40
BCG-M37	M37×1.5	18-25	9	40
BCG-M40	M40×1.5	22-28、18-25、22-30、25-32	9、9、10、10	43、43、45、50
BCG-M42	M42×1.5	22-28	9	45
BCG-M48	M48×1.5	25-32	10	52
BCG-M50	M50×1.5	25-32、32-38	10、12	55、58
BCG-M54	M54×1.5	32-38	12	58
BCG-M56	M56×1.5	32-38	12	58
BCG-M60	M60×1.5	37-44	12	64
BCG-M63	M63×1.5	37-44、42-53	12、15	68、78
BCG-M64	M64×1.5	37-44	12	68
BCG-M72	M72×1.5	42-52	15	78
BCG-M75	M75×1.5	42-52	15	78
BCG-M76	M76×1.5	42-52	15	78
BCG-M80	M80×1.5	55-60	17	88
BCG-M85	M85×1.5	65-70	98	17/18
BCG-M88	M88×1.5	65-70	98	40/43
BCG-M100	M100×1.5	75-80	110	43