



- 產品材質：采用黃銅加工，表面鍍鎳；TPE塑料，改性橡膠
- 防護等級：IP68
- 產品性能：固定纜線，防液體滲漏，耐腐蝕，機械強度高，通過RoHS測試

- Type-BCG  
BCG is the connector which is used to secure the cable
- Material: Brass, nickel surface, TPE plastics, rubber modified
- Protection Degree: IP68
- Properties: Secure the cable, liquid tight, corrosion resistance, high mechanical strength, Passed RoHS

TYPE BCG-G (銅制電纜接頭)

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
BCG-G1/4	G1/4	3~7	6	14
BCG-G3/8	G3/8	4~8, 6~10	7, 7	18
BCG-G1/2	G1/2	8~12, 4~8, 10~14	8, 8, 8	22, 22, 24
BCG-G3/4	G3/4	13~18	8	30
BCG-G1	G1	15~22	9	36
BCG-G1-1/4	G1-1/4	22~30	10	45
BCG-G1-1/2	G1-1/2	25~32, 18~25	10, 10	50, 50
BCG-G2	G2	37~44	12	64
BCG-G2-1/2	G1-1/2	42~52	15	78
BCG-G3	G3	65~70	18	98

TYPE BCG-N (銅制電纜接頭)

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
BCG-N1/4	NPT1/4	3~7	6	14
BCG-N3/8	NPT3/8	4~8, 6~10	7, 7	18
BCG-N1/2	NPT1/2	8~12, 4~8, 10~14	8, 8, 8	22, 22, 24
BCG-N3/4	NPT3/4	13~18	8	30
BCG-N1	NPT1	15~22	9	36
BCG-N1-1/4	NPT1-1/4	22~28	10	45
BCG-N1-1/2	NPT1-1/2	25~32, 18~25	10, 10	50, 50
BCG-N2	NPT2	37~44	12	64
BCG-N2-1/2	NPT1-1/2	42~52	15	78
BCG-N3	NPT3	65~70	18	98