



TYPE BSF型 (內螺紋接頭)

■ 產品材質:

採用黃銅加工，表面鍍鎳，TPE塑料，改性橡膠

■ 防護等級: IP66

■ 產品性能: 防液體滲漏，耐腐蝕，機械强度高，
通過RoHS測試

■ 適用範圍: 適用於C型和W型防水金屬軟管于設備的連接

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSF-12	3/8"	G3/8	M20*1.5
BSF-16	1/2"	G1/2	M20*1.5
BSF-20	3/4"	G3/4	M25*1.5
BSF-25	1"	G1	M32*1.5(2)
BSF-32	1-1/4"	G1-1/4	M40*1.5(2)
BSF-38	1-1/2"	G1-1/2	M50*1.5(2)
BSF-51	2"	G2	M63*1.5(2)
BSF-64	2-1/2"	G2-1/2	M75*1.5(2)
BSF-75	3"	G3	M85*1.5(2)
BSF-100	4"	G4	M100*1.5(2)

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSF-12	3/8"	5/8"-24UNEF	3/4"-20UNEF
BSF-12	3/8"	7/8"-20UNEF	1"-20UNEF
BSF-12	3/8"	13/16"-18UNEF	
BSF-16	1/2"	1"-20UNEF	13/16"-18UNEF
BSF-16	1/2"	17/16"-18UNEF	
BSF-20	3/4"	13/16"-18UNEF	17/16"-18UNEF
BSF-25	1"	17/16"-18UNEF	
BSF-32	1-1/4"	1-3/4"-18UNEF	
BSF-38	1-1/2"	2"-18UNEF	

□ Type-BSF

BSF is suitable for the liquidtight metallic conduit type C and type W.

□ Material: Brass,nickel surface,TPE plastics;
rubber modified.

□ Protection Degree: IP66

□ Properties: Liquidtight , corrosion resistance,high
mechanical strength.
Passed RoHS