


**銅製防水型鎖緊式接頭(BSL型)**  
Liquidtight End Connector (TYPE BSL)

**SONGYAM**



TYPE BSL (鎖緊式接頭)

- **產品材質:** 採用黃銅加工，表面鍍鎳；TPE塑料，改性橡膠
- **防護等級:** IP66
- **產品性能:** 鎖緊電纜防液體滲漏，耐腐蝕，機械强度高，通過RoHS測試
- **適用範圍:** 適用於C型和W型防水金屬軟管于設備的连接

Type-BSL

BSL is suitable for the liquidtight metallic conduit type C and type W.

- Material:** Brass, nickel surface ; TPE plastics, rubber modified.
- Protection Degree:** IP66
- Properties:** Locking cable , liquidtight , corrosion resistance,high mechanical strength.  
Passed RoHS

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSL-10	5/16"	G5/16	M16*1.5
BSL-12	3/8"	G3/8	M20*1.5
BSL-16	1/2"	G1/2	M20*1.5
BSL-20	3/4"	G3/4	M25*1.5
BSL-25	1"	G1	M32*1.5(2)
BSL-32	1-1/4"	G1-1/4	M40*1.5(2)
BSL-38	1-1/2"	G1-1/2	M50*1.5(2)
BSL-51	2"	G2	M63*1.5(2)
BSL-64	2-1/2"	G2-1/2	M75*1.5(2)
BSL-75	3"	G3	M85*1.5(2)
BSL-100	4"	G4	M100*1.5(2)

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSL-10	5/16"	NPT5/16	PG9
BSL-12	3/8"	NPT3/8	PG11/PG13.5
BSL-16	1/2"	NPT1/2	PG16/PG19
BSL-20	3/4"	NPT3/4	PG21
BSL-25	1"	NPT1	PG29
BSL-32	1-1/4"	NPT1-1/4	PG36
BSL-38	1-1/2"	NPT1-1/2	PG42
BSL-51	2"	NPT2	PG48
BSL-64	2-1/2"	NPT2-1/2	PG63
BSL-75	3"	NPT3	
BSL-100	4"	NPT4	