



TYPE BSM (外螺紋接頭)

- **產品材質:** 採用黃銅加工，表面鍍鎳；TPE塑料，改性橡膠；
- **防護等級:** IP66
- **產品性能:** 防液體滲漏，耐腐蝕，機械强度高，通過RoHS測試
- **適用範圍:** 適用於C型和W型防水金屬軟管于設備的連接

Type-BSM

BSM is suitable for the liquidtight metallic conduit type C and type W .

- Material:** Brass, nickel surface ; TPE plastics, rubber modified
- Protection Degree:** IP66
- Properties:** Liquidtight , corrosion resistance,high mechanical strength.
Passed RoHS

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSM-8	1/4"	G1/4	M16*1.5
BSM-10	5/16"	G5/16	M16*1.5
BSM-12	3/8"	G3/8	M20*1.5
BSM-16	1/2"	G1/2	M20*1.5
BSM-20	3/4"	G3/4	M25*1.5
BSM-25	1"	G1	M32*1.5(2)
BSM-32	1-1/4"	G1-1/4	M40*1.5(2)
BSM-38	1-1/2"	G1-1/2	M50*1.5(2)
BSM-51	2"	G2	M63*1.5(2)
BSM-64	2-1/2"	G2-1/2	M75*1.5(2)
BSM-75	3"	G3	M85*1.5(2)
BSM-100	4"	G4	M100*1.5(2)

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
BSM-8	1/4"	NPT1/4	PG7
BSM-10	5/16"	NPT5/16	PG9
BSM-12	3/8"	NPT3/8	PG11/PG13.5
BSM-16	1/2"	NPT1/2	PG16/PG19
BSM-20	3/4"	NPT3/4	PG21
BSM-25	1"	NPT1	PG29
BSM-32	1-1/4"	NPT1-1/4	PG36
BSM-38	1-1/2"	NPT1-1/2	PG42
BSM-51	2"	NPT2	PG48
BSM-64	2-1/2"	NPT2-1/2	PG63
BSM-75	3"	NPT3	
BSM-100	4"	NPT4	