

抗拉型防水金屬軟管 (CI型)

Tensile Strength Liquidtight Flexible Metal Conduit (TYPE CI)

SONGYAM



CI型軟管 其特殊的扣合方式使其具有極高的抗拉能力和防機械損傷性能，為其中的導體提供了更好的保護。
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
CI-12	3/8"	12.3	18.0	50	50
CI-16	1/2"	15.8	21.3	65	50
CI-20	3/4"	20.6	26.7	85	50
CI-25	1"	26.4	33.4	105	50
CI-32	1-1/4"	34.2	42.2	135	20
CI-38	1-1/2"	40.0	48.3	160	20
CI-51	2"	51.0	60.3	200	20
CI-64	2-1/2"	63.0	73.0	250	10
CI-75	3"	76.8	88.9	320	10
CI-100	4"	98.5	114.3	400	10

■ 產品構造：其內核由鍍鋅鋼帶反鎖繞製而成，以增加其抗拉強度，外部被覆PVC。

■ 工作溫度：-25°C ~ 105°C

■ 阻燃等級：V0 (UL94),GB8624 B2

■ 防護等級：IP68

■ 顏色：黑色、灰色，其他顏色可以根據需求而定。

Type-CI

CI is has jacket tension flexible metal conduit

Structure: Its core consists of galvanized steel locked around the system to increase its tensile strength. External coating PVC.

Temperature Range: -25°C ~ 105°C

Flame-retardant: V0(UL94),GB8624 B2

Protection Degree IP68

Standard Color:Black and gray. Other colors available upon request.

Properties or Applications:Type-CI conduit engaging its special way so that it has a very high tensile strength properties and mechanical damage, as one of the conductor to provide better protection of their external sunscreen PVC materials can ensure long-term outdoor hose be used.

Passed RoHS

