

## 防爆型金屬軟管 (EXM型 / EXS型)

Explosion-proof Flexible Metal Conduit (TYPE EXM / TYPE EXS)

SONGYAM



EXM型/EXS型 具有防爆、耐腐蝕、耐高溫，高的機械強度，適用於安全性高的場所，如：化工、煤礦、核電、鋼鐵、冶煉、焊接等。通過RoHS測試。

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
EXM (EXS) -10	5/16"	10.0	16.0	40	50
EXM (EXS) -12	3/8"	12.2	18.0	50	60
EXM (EXS) -16	1/2"	16.0	22.2	65	50
EXM (EXS) -20	3/4"	20.3	27.0	80	50
EXM (EXS) -25	1"	25.5	33.0	105	50
EXM (EXS) -32	1-1/4"	32.5	41.0	130	25
EXM (EXS) 38	1-1/2"	38.0	47.3	160	25
EXM (EXS) -51	2"	60.4	60.7	205	20
EXM (EXS) 64	2-1/2"	62.5	73.6	250	10
EXM (EXS) -75	3"	75.0	87.0	300	10
EXM (EXS)-100	4"	98.5	112.0	400	10

■ 產品構造：EXM型其內核為加厚熱鍍鋅鋼帶繞制而成，外部不鏽鋼編織加固。

EXS型其內核為加厚不鏽鋼帶繞制而成，外部不鏽鋼編織加固。

■ 工作溫度：最高溫度250℃

■ 防護等級：IP40

### □ Type-EXM (EXS)

EXM (EXS) is the non-liquidtight explosior-pro of flexible steel conduit.

□ Structure: Its core is thicker heat galvanized steel strip or stainless steel strip around the system, external stainless steel braided reinforcement.

□ Temperature Range Range: Up to 250℃

□ Protection Degree: IP40

□ Properties or Applications: EXM (EXS) conduit with explosion-proof, corrosion resistance, high temperature resistance, high mechanical strength for safe place, such as chemical, coal, nuclear power, steel, metallurgy, welding, etc.

Passed RoHS

