

■ 阻燃尼龍軟管 (FPA型)

Flame-retardant Nylon Tubing (TYPE FPA)

SONGYAM



FPA型軟管 自熄滅性非常好。完全滿足高安全性要求，不含鹵素和磷。表面有光澤，高韌性，抗扭曲，機器强度高，耐油，耐碱，耐弱酸等。適用於：機械設備，電氣絕緣保護，空調制冷設備，地鐵，電力機車等。
通過RoHS測試

型號 Type	內徑 Inner(mm)	外徑 Outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
FPA-10.0	6.5	10.0	13	100
FPA-13.0	10.0	13.0	20	100
FPA-15.8	12.0	15.8	35	100
FPA-18.5	14.3	18.5	40	100
FPA-21.2	17.0	21.2	45	100
FPA-25.5	21.0	25.5	50	50
FPA-28.5	23.0	28.5	55	50
FPA-34.5	29.0	34.5	65	50
FPA-42.5	36.0	42.5	90	25
FPA-54.5	48.0	54.5	100	25

- 產品材質：阻燃尼龍6
- 工作溫度：-40℃~115℃
- 阻燃等級：V0(UL94)
- 防護等級：IP68
- 產品顏色：黑色、灰色，其他顏色可以根據需要而定。



Type-FPA

FPA is used to protect the wire plastic tubing

- Material: Flame-retardant nylon 6
- Color: Black and gray, Other colors available upon request.
- Temperature: -40℃~115℃
- Fire-retardant: V0(UL94)
- Protection Degree: IP68
- Properties or Applications:

Type-FPA tubing self extinguishing is very good, meet the safety requirements, free of halogen and phosphorus, passed RoHS testing, surface gloss, high toughness, anti-distortion, high mechanical strength, oil-resistant, weak acid and alkaline resistance, etc., suitable for mechanical manufacture, and equipment, electrical insulation, air conditioning and refrigeration equipment, subway, electric locomotives.

Passed RoHS