

阻燃聚丙烯軟管 (FPP型)

Flame-retardant Polypropylene Tubing (TYPE FPP)

SONGYAM



FPP型軟管 自熄滅性非常好，完全滿足高安全性要求，不含鹵素和磷，耐油、耐酸鹼、耐化學腐蝕性能好、機械強度好、廣泛用於：化工設備，機械製造等。

通過RoHS測試

型號 Type	內徑 Inner(mm)	外徑 Outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
FPP-10.0	6.5	10.0	13	100
FPP-13.0	10.0	13.0	20	100
FPP-15.8	12.0	15.8	35	100
FPP-18.5	14.3	18.5	40	100
FPP-21.2	17.0	21.2	45	100
FPP-25.5	21.0	25.5	50	50
FPP-28.5	23.0	28.5	55	50
FPP-34.5	29.0	34.5	65	50
FPP-42.5	36.0	42.5	90	25
FPP-54.5	48.0	54.5	100	25

- 產品材質：阻燃聚丙烯
- 工作溫度：-40℃~110℃
- 阻燃等級：V0(UL94)
- 防護等級：IP68
- 產品顏色：黑色、灰色，其他顏色可以根據需要而定。

Type-FPP

FPP is used to protect the wire plastic tubing

- Material: Flame-retardant polypropylene
- Color: Black and gray, Other colors available upon request.
- Temperature: -40℃~110℃
- Fire-retardant: V0(UL94)
- Protection Degree: IP68
- Properties or Applications:

Type-FPP tubing self extinguishing is very good, meet the safety requirements, free of halogen and phosphorus, passed RoHS testing, oil resistance, acid and alkaline resistance, good resistance to chemical corrosion, good mechanical strength, widely used for: chemical equipment, mechanical manufacture etc.

