

UL1型金屬軟管 (ML型) UL1 Flexible Metal Conduit (TYPE ML)


SONGYAM



ML型軟管 依照美國UL1標準製造，耐腐蝕、耐高溫、具有極高的抗機械損傷能力，被廣泛應用於各領域。
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min.innner(mm)	最大外徑 Max.outter(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
ML-12	3/8"	9.52	15.40	50	50
ML-16	1/2"	15.88	23.37	75	50
ML-20	3/4"	20.62	28.07	100	50
ML-25	1"	25.40	35.05	125	50
ML-32	1-1/4"	31.75	41.40	160	25
ML-38	1-1/2"	38.10	49.53	190	25
ML-51	2"	50.80	62.23	255	20
ML-64	2-1/2"	63.50	77.72	320	10
ML-75	3"	76.20	90.42	380	10
ML-90	3-1/2"	88.90	103.12	445	10
ML-100	4"	101.60	115.82	570	10

- 產品構造：厚熱鍍鋅鋼帶繞製而成
- 工作溫度：最高溫度250°C
- 防護等級：IP40



Type-ML

ML is the UL1 flexible steel conduit.

- Structure: Helically formed from thick hot-dipped galvanized steel strip.
- Temperature Range: Up to 250°C
- Protection Degree: IP40
- Properties or Applications: Type-ML conduit in accordance with U.S. standards for manufacturing, corrosion resistance, high temperature, with a high resistance to mechanical damage ability, is widely used in various fields.
Passed RoHS