

輕型金屬軟管 (MR型)

Lightweight Flexible Metal Conduit (TYPE MR)

SONGYAM



MR型軟管 具有良好的機械強度，耐腐蝕，耐高溫。適用於溫度較高、濕度較低的工作環境，如：鋼鐵、冶煉、樓宇消防設施、照明設備等。通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
MR-6	3/16"	6.0	8.2	25	100
MR-8	1/4"	7.8	11.0	35	100
MR-10	5/16"	10.2	13.4	40	50
MR-12	3/8"	12.0	15.3	50	50
MR-16	1/2"	15.6	19.3	65	50
MR-20	3/4"	19.7	23.3	80	50
MR-25	1"	25.2	29.7	100	50
MR-32	1-1/4"	32.2	37.6	130	25
MR-38	1-1/2"	38.1	44.8	152	25
MR-51	2"	50.8	58.2	200	20
MR-64	2-1/2"	62.5	71.1	250	10
MR-75	3"	75.0	84.3	300	10
MR-100	4"	98.0	109.0	390	10

■ 產品構造：熱鍍鋅鋼帶繞製而成

■ 工作溫度：最高溫度250°C

■ 防護等級：IP40

Type-MR

MR is the non-jacket flexible steel conduit.

Structure Helically formed from hot-dipped galvanized steel strip

Temperature Range: Up to 250°C

Protection Degree: IP40

Properties or Applications: Type-MR conduit has good mechanical strength, corrosion resistance, high temperature resistance, suitable for high temperature, low humidity work environment, such as steel, metallurgy, building fire safety facilities, lighting equipment.

Passed RoHS

