

不銹鋼金屬軟管 (MS型)

Stainless Steel Flexible Metal Conduit (TYPE MS)


SONGYAM



MS型軟管 具有良好的耐腐蝕性、耐高溫、機械
强度高、適用於高溫高濕、高腐蝕的工作環境，
如：化工、鋼鐵、冶煉、船舶等場所。
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
MS-6	3/16"	5.9	8.2	25	100
MS-8	1/4"	7.8	11.0	35	100
MS-10	5/16"	10.0	13.4	40	50
MS-12	3/8"	12.4	15.3	50	50
MS-16	1/2"	15.4	19.3	65	50
MS-20	3/4"	20.0	23.3	80	50
MS-25	1"	25.0	29.7	100	50
MS-32	1-1/4"	32.0	37.6	130	25
MS-38	1-1/2"	38.0	44.8	152	25
MS-51	2"	51.0	58.2	200	20
MS-64	2-1/2"	62.5	71.1	250	10
MS-75	3"	75.0	84.3	300	10
MS-100	4"	98.0	109.0	390	10

- 產品構造：由SUS304不銹鋼帶繞製而成
- 工作溫度：最高溫度600°C
- 防護等級：IP40



Type-MS

MS is the non-jacket flexible stainless steel conduit.

Structure Helically formed from SUS 304 stainless steel strip

Temperature Range: UP to 600 C

Protection Degree IP40

Properties or Applications: Type -MS conduit has good corrosion resistance, high temperature resistance, high mechanical strength, suitable for high temperature and humidity, high corrosion work environment, such as chemical, steel, metallurgy, shipbuilding and other places.

Passed RoHS