



TYPE MSM (外螺紋接頭)

Type- MSM

MSM is suitable for the liquidtight metallic conduit type C and type W

Material: Malleable cast iron, hot -dipped galvanized surface, TPE plastics.

Protection Degree: IP66

Properties: Liquidtight, corrosion resistance, high mechanical strength.

Passed RoHS

■ 產品材質: 採用可鍛鑄鐵壓鑄而成, 表面熱鍍鋅, TPE塑料。

■ 防護等級: IP66

■ 產品性能: 防液體滲漏, 耐腐蝕, 機械强度高, 通過RoHS測試

■ 適用範圍: 適用於C型和W型防水金屬軟管于設備的連接

型號 Type	適配軟管 For conduit size	螺紋 Thread size
MSM -12	3/8"	NPT1/2
MSM -16	1/2"	NPT1/2
MSM -20	3/4"	NPT3/4
MSM -25	1"	NPT1
MSM -32	1-1/4"	NPT1-1/4
MSM -38	1-1/2"	NPT1-1/2
MSM -51	2"	NPT2
MSM -64	2-1/2"	NPT2-1/2
MSM -75	3"	NPT3
MSM -100	4"	NPT4



TYPE MSL (外螺紋接頭90°)

Type-MSL

MSL is suitable for the liquidtight metallic conduit type C and type W

Material: Malleable cast iron, hot -dipped galvanized surface, TPE plastics.

Protection Degree: IP66

Properties: Liquidtight, corrosion resistance, high mechanical strength.

Passed RoHS

■ 產品材質: 採用可鍛鑄鐵壓鑄而成, 表面熱鍍鋅, TPE塑料。

■ 防護等級: IP66

■ 產品性能: 防液體滲漏, 耐腐蝕, 機械强度高, 通過RoHS測試

■ 適用範圍: 適用於C型和W型防水金屬軟管于設備的連接
另有MSH外螺紋接頭45° 可供選擇

型號 Type	適配軟管 For conduit size	螺紋 Thread size
MSL -12	3/8"	NPT1/2
MSL -16	1/2"	NPT1/2
MSL -20	3/4"	NPT3/4
MSL -25	1"	NPT1
MSL -32	1-1/4"	NPT1-1/4
MSL -38	1-1/2"	NPT1-1/2
MSL -51	2"	NPT2
MSL -64	2-1/2"	NPT2-1/2
MSL -75	3"	NPT3
MSL -100	4"	NPT4