



- 產品材質：采用尼龍制成
- 防護等級：IP66
- 產品性能：耐腐蝕，機械强度高，通過RoHS測試
- 適用範圍：適用於P型塑料波紋管于設備的連接

Type-NQSM

NQSM nonmetallic connector is suitable for the nonmetallic connector type P.

- Material: Nylon
- Protection Degree: IP66
- Properties: Corrosion resistance, high mechanical strength, passed RoHS

NQSM-P (尼龍快速接頭)
TYPE NQSM-P

型號 Type	適配軟管 For conduit size	螺紋 Thread size
NQSM-AD10.0 P	AD10.0	PG7
NQSM-AD13.0 P	AD13.0	PG7/PG9/PG11/PG13.5
NQSM-AD15.8 P	AD15.8	PG11/PG13.5
NQSM-AD18.5 P	AD18.5	PG13.5
NQSM-AD21.2 P	AD21.2	PG13.5/PG16
NQSM-AD25.5 P	AD25.5	PG21
NQSM-AD28.5 P	AD28.5	PG21
NQSM-AD34.5 P	AD34.5	PG29
NQSM-AD42.5 P	AD42.5	PG36
NQSM-AD54.5 P	AD54.5	PG42/PG48

NQSM-G (尼龍快速接頭)
TYPE NQSM-G

型號 Type	適配軟管 For conduit size	螺紋 Thread size
NQSM-AD10.0 G	AD10.0	G1/4
NQSM-AD13.0 G	AD13.0	G3/8
NQSM-AD15.8 G	AD15.8	G3/8 G1/2
NQSM-AD18.5 G	AD18.5	G1/2
NQSM-AD21.2 G	AD21.2	G1/2
NQSM-AD25.5 G	AD25.5	
NQSM-AD28.5 G	AD28.5	G3/4
NQSM-AD34.5 G	AD34.5	G1
NQSM-AD42.5 G	AD42.5	G1-1/4 G1-1/2
NQSM-AD54.5 G	AD54.5	G2