



- 產品材質：采用尼龍制成
- 防護等級：IP66
- 產品性能：防液體滲漏、耐腐蝕，機械强度高，通過RoHS測試
- 適用範圍：適用於P型塑料波紋管于設備的連接

- Type-NWSM
NWSM nonmetallic connector is suitable for the nonmetallic connector type P.
- Material: Nylon
- Protection Degree: IP66
- Properties: : Liquidtight ,corrosion resistance,high mechanical strength, passed RoHS

NWSM-P (尼龍防水接頭)
TYPE NWSM-P

型號 Type	適配軟管 For conduit size	螺紋 Thread size
NWSM-AD10.0 P	AD10.0	PG7/PG9
NWSM-AD13.0 P	AD13.0	PG11
NWSM-AD15.8 P	AD15.8	PG13.5/PG16
NWSM-AD18.5 P	AD18.5	PG13.5/PG16
NWSM-AD21.2 P	AD21.2	PG16/ PG21
NWSM-AD25.5 P	AD25.5	PG21
NWSM-AD28.5 P	AD28.5	PG21
NWSM-AD34.5 P	AD34.5	PG29
NWSM-AD42.5 P	AD42.5	PG36/ PG42
NWSM-AD54.5 P	AD54.5	PG48

NWSM-PF (尼龍防水接頭)
TYPE NWSM-PF

型號 Type	適配軟管 For conduit size	螺紋 Thread size
NWSM-AD10.0 PF	AD10.0	PF1/4
NWSM-AD13.0 PF	AD13.0	PF3/8
NWSM-AD15.8 PF	AD15.8	PF1/2
NWSM-AD18.5 PF	AD18.5	PF1/2
NWSM-AD21.2 PF	AD21.2	PF1/2 PF3/4
NWSM-AD25.5 PF	AD25.5	PF3/4
NWSM-AD28.5 PF	AD28.5	PF3/4
NWSM-AD34.5 PF	AD34.5	PF1
NWSM-AD42.5 PF	AD42.5	PF1-1/4 PF1-1/2
NWSM-AD54.5 PF	AD54.5	PF2