



PA型軟管 不含鹵素和磷，表面光澤，高韌性，抗扭曲，機械强度高，耐油，耐碱，耐弱酸等。適用於：機械制造，電氣絕緣保護，電氣自動化控制系統，空調制冷設備，公共交通設備，地鐵電力機車等。
通過RoHS測試

型號 Type	內徑 Inner(mm)	外徑 Outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coll(m)
PA-10.0	6.5	10.0	13	100
PA-13.0	10.0	13.0	20	100
PA-15.8	12.0	15.8	35	100
PA-18.5	14.3	18.5	40	100
PA-21.2	17.0	21.2	45	100
PA-25.5	21.0	25.5	50	50
PA-28.5	23.0	28.5	55	50
PA-34.5	29.0	34.5	65	50
PA-42.5	36.0	42.5	90	25
PA-54.5	48.0	54.5	100	25

- 產品材質：尼龍6
- 工作溫度：-40°C~115°C
- 阻燃等級：HB(UL94)
- 防護等級：IP68
- 產品顏色：黑色、灰色，其他顏色可以根據需要而定。



Type-PA

PA is used to protect the wire plastic tubing

Material: Nylon 6

Color: Black and gray, Other colors available upon request.

Temperature: -40°C ~ 115°C

Fire-retardant: HB(UL94)

Protection Degree: IP68

Properties or Applications:

Type-PA tubing free of halogen and phosphor, passed RoHS testing, surface gloss, high toughness, anti-distortion, high mechanical strength, oil-resistant, weak acid and alkaline resistance, etc, suitable for mechanical manufacture, electrical insulation, electrical automation control systems, air conditioning and refrigeration equipment, public transportation, subway electric locomotive.

Passed RoHS