



- **產品材質:** 採用不銹鋼304加工, TPE塑料, 改性橡膠
- **防護等級:** IP68
- **產品性能:** 固定纜纜, 防液體滲漏, 耐腐蝕, 機械強度, 通過RoHS測試
- Type-SCG**
SCG is the connector which is used to secure the cable
- Material:** 304 stainless steel ; TPE plastics, rubber modified
- Protection Degree:** IP66
- Properties:** Secure the cable, liquid tight, corrosion resistance, high mechanical strength. Passed RoHS

TYPE SCG-M (不銹鋼電纜接頭)

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
SCG-M8	M8×1.0	3-7	6	14
SCG-M10	M10×1.0	3-7	6	14
SCG-M12	M12×1.5	3-7	6	14
SCG-M14	M14×1.5	3-7	6	16
SCG-M16	M16×1.5	4-8、6-10	7	18、20
SCG-M18	M18×1.5	6-10	7	20
SCG-M20	M20×1.5	8-12、4-8、6-10、10-14	8、7、7、7	22、22、22、24
SCG-M22	M22×1.5	10-14、8-12	8、8	24、24
SCG-M24	M24×1.5	10-14	8	27
SCG-M25	M25×1.5	10-14、10-16、13-18	8、8、8	27、28、30
SCG-M27	M27×1.5	13-18、10-16	8	30、30
SCG-M30	M30×1.5	13-18、10-16、15-20	8、8、8	34、34、34
SCG-M32	M32×1.5	15-22、13-18、18-25	9、8、9	34、34、40
SCG-M33	M33×1.5	15-22	9	36
SCG-M36	M36×1.5	18-25、15-22	9	40、40
SCG-M37	M37×1.5	18-25	9	40
SCG-M40	M40×1.5	22-28、18-25、22-30、25-32	9、9、10、10	43、43、45、50
SCG-M42	M42×1.5	22-28	9	45
SCG-M48	M48×1.5	25-32	10	52
SCG-M50	M50×1.5	25-32、32-38	10、12	55、58
SCG-M54	M54×1.5	32-38	12	58
SCG-M56	M56×1.5	32-38	12	58
SCG-M60	M60×1.5	37-44	12	64
SCG-M63	M63×1.5	37-44、42-53	12、15	68、78
SCG-M64	M64×1.5	37-44	12	68
SCG-M72	M72×1.5	42-52	15	78
SCG-M75	M75×1.5	42-52	15	78
SCG-M76	M76×1.5	42-52	15	78
SCG-M80	M80×1.5	55-60	17	88
SCG-M85	M85×1.5	65-70	98	17/18
SCG-M88	M88×1.5	65-70	98	40/43
SCG-M100	M100×1.5	75-80	110	43