



- 產品材質：采用不銹鋼304加工，TPE塑料，改性橡膠
- 防護等級：IP68
- 產品性能：固定纜纜，防液體滲漏，耐腐蝕，機械强度高，通過RoHS測試

Type-SCG

SCG is the connector which is used to secure the cable

Material: 304 stainless steel ; TPE plastics, rubber modified

Protection Degree: IP66

Properties: Secure the cable, liquid tight, corrosion resistance, high mechanical strength.

Passed RoHS

TYPE SCG-G (不銹鋼電纜接頭)

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
SCG-G1/4	G1/4	3~7	6	14
SCG-G3/8	G3/8	4~8, 6~10	7, 7	18
SCG-G1/2	G1/2	8~12, 4~8, 10~14	8, 8, 8	22, 22, 24
SCG-G3/4	G3/4	13~18	8	30
SCG-G1	G1	15~22	9	36
SCG-G1-1/4	G1-1/4	22~30	10	45
SCG-G1-1/2	G1-1/2	25~32, 18~25	10, 10	50, 50
SCG-G2	G2	37~44	12	64
SCG-G2-1/2	G2-1/2	42~52	15	78
SCG-G3	G3	65~70	18	98

TYPE SCG-N (不銹鋼電纜接頭)

型號 Type	螺紋規格 Thread size	卡口範圍 Clamping range (mm)	螺紋長度 GL (mm)	扳手尺寸 Wrench size (mm)
SCG-N1/4	NPT1/4	3~7	6	14
SCG-N3/8	NPT3/8	4~8, 6~10	7, 7	18
SCG-N1/2	NPT1/2	8~12, 4~8, 10~14	8, 8, 8	22, 22, 24
SCG-N3/4	NPT3/4	13~18	8	30
SCG-N1	NPT1	15~22	9	36
SCG-N1-1/4	NPT1-1/4	22~28	10	45
SCG-N1-1/2	NPT1-1/2	25~32, 18~25	10, 10	50, 50
SCG-N2	NPT2	37~44	12	64
SCG-N2-1/2	NPT2-1/2	42~52	15	78
SCG-N3	NPT3	65~70	18	98