




TYPE SSM-A (外螺紋接頭)



TYPE SSM-B (外螺紋接頭)



- **產品材質：** 採用不銹鋼304加工，TPE塑料，改性橡膠。
- **防護等級：** IP66
- **產品性能：** 防液體滲漏，耐腐蝕，機械强度高，通過RoHS測試
- **適用範圍：** 適用於C型和W型防水金屬軟管于設備的连接

Type-SSM

SSM is suitable for the liquidtight metallic conduit type C and type W.

- Material:** 304 Stainless steel; TPE plastics, rubber modified

- Protection Degree:** IP66

- Properties:** Liquidtight, corrosion resistance, high mechanical strength.
Passed RoHS

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
SSM-8	1/4"	G1/4	M16*1.5
SSM-10	5/16"	G5/16	M16*1.5
SSM-12	3/8"	G3/8	M20*1.5
SSM-16	1/2"	G1/2	M20*1.5
SSM-20	3/4"	G3/4	M25*1.5
SSM-25	1"	G1	M32*1.5(2)
SSM-32	1-1/4"	G1-1/4	M40*1.5(2)
SSM-38	1-1/2"	G1-1/2	M50*1.5(2)
SSM-51	2"	G2	M63*1.5(2)
SSM-64	2-1/2"	G2-1/2	M75*1.5(2)
SSM-75	3"	G3	M85*1.5(2)
SSM-100	4"	G4	M100*1.5(2)

型號 Type	適配軟管 For conduit size	螺紋 Thread size	螺紋 Thread size
SSM-8	1/4"	NPT1/4	PG7
SSM-10	5/16"	NPT5/16	PG9
SSM-12	3/8"	NPT3/8	PG11/PG13.5
SSM-16	1/2"	NPT1/2	PG16PG19
SSM-20	3/4"	NPT3/4	PG21
SSM-25	1"	NPT1	PG29
SSM-32	1-1/4"	NPT1-1/4	PG36
SSM-38	1-1/2"	NPT1-1/2	PG42
SSM-51	2"	NPT2	PG48
SSM-64	2-1/2"	NPT2-1/2	PG63
SSM-75	3"	NPT3	
SSM-100	4"	NPT4	