

耐寒型防水金屬軟管 (WA型)

Cold-resistant Liquidtight Flexible Metal Conduit (TYPE WA)

SONGYAM



WA型軟管 適合在高寒的環境中使用，耐寒性特別出色，並具有高的機械強度。
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coll(m)
WA-6	3/16"	6.0	9.2	20	100
WA-8	1/4"	8.1	12.2	25	100
WA-10	5/16"	10.0	14.2	30	100
WA-12	3/8"	12.2	16.5	35	50
WA-16	1/2"	16.0	20.5	50	50
WA-20	3/4"	20.3	25.7	60	50
WA-25	1"	25.5	31.7	80	50
WA-32	1-1/4"	32.5	39.5	90	25
WA-38	1-1/2"	38.0	46.5	110	25
WA-51	2"	50.4	60.0	150	20
WA-64	2-1/2"	62.5	73.0	190	10
WA-75	3"	75.0	87.0	220	10
WA-100	4"	98.5	113.0	300	10

- **產品構造:** 其內核由鍍鋅鋼帶繞製而成，獨特的真空擠出工藝使得軟管外部覆上一層高耐寒PVC，且不影響導管的彎曲性。
- **工作溫度:** -55°C ~ 80°C
- **燃燒等級:** V0(UL94),GB8624 B2
- **防護等級:** IP68
- **顏色:** 黑色、灰色，其他顏色可以根據需求而定



- Type-WA**
WA is cold-resistant jacket hot-dipped galvanized steel conduit for high-flex
- Structure:** Its core consists of thick hot-dipped galvanized steel, external covered with a layer of cold-resistant PVC.
- Temperature Range:** -55°C ~ 80°C
- Flame-retardant:** V0(UL94),GB8624 B2
- Protection Degree:** IP68
- Standard Color:** Black and gray. Other colors available upon request
- Properties or Applications:** Type-WA conduit is suitable for use in cold environments, cold particularly outstanding, and has a high mechanical strength.
Passed RoHS