

## 低煙無鹵防水金屬軟管(WH型)

Low Smoke And Halogen-Free Liquidtight Flexible Metal Conduit (TYPE WH)

SONGYAM



WH型軟管 其被覆塑料具有低煙無鹵的特性，是保障人類生命財產的安全產品。  
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
WH-6	3/16"	6.0	9.2	20	100
WH-8	1/4"	8.1	12.2	25	100
WH-10	5/16"	10.0	14.2	30	100
WH-12	3/8"	12.2	16.5	35	50
WH-16	1/2"	16.0	20.5	50	50
WH-20	3/4"	20.3	25.7	60	50
WH-25	1"	25.5	31.7	80	50
WH-32	1-1/4"	32.5	39.5	90	25
WH-38	1-1/2"	38.0	46.5	110	25
WH-51	2"	50.4	60.0	150	20
WH-64	2-1/2"	62.5	73.0	190	10
WH-75	3"	75.0	87.0	220	10
WH-100	4"	98.5	113.0	300	10

- **產品構造：** 其內核由熱鍍鋅鋼帶繞製而成，獨特的真空擠出工藝使得軟管外部覆上一層低煙無鹵性塑料而不影響導管的彎曲性。
- **工作溫度：** -25°C ~ 90°C
- **燃燒等級：** V0(UL94),GB8624 B2
- **防護等級：** IP68
- **顏色：** 黑色、灰色，其他顏色可以根據需求而定。



### Type-WH

WH is low smoke and halogen-free jacket hot-dipped galvanized steel conduit for high-flex

- Structure:** Its core consists of thick hot-dipped galvanized steel external covered with a layer of low smoke and halogen-free plastic

- Temperature Range:** -25°C ~ 90°C

- Flame-retardant:** V0(UL94),GB8624 B2

- Protection Degree** IP68

- Standard Color** Black and gray. Other colors available upon request.

- Properties or Applications:** Type-WH conduit With a liquidtight function, and its coating plastic with low smoke and halogen-free characteristics, is to protect human life and property safety products sent. Passed RoHS