

## ■ 耐油型防水金屬軟管 (WO型)

Oil-resistant Liquidtight Flexible Metal Conduit (TYPE WO)

SONGYAM



WO型軟管 具有防液體滲漏功能。高的耐油性，機械强度高。適用一般工業用機油及切削油。通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
WO-6	3/16"	6.0	9.2	20	100
WO-8	1/4"	8.1	12.2	25	100
WO-10	5/16"	10.0	14.2	30	100
WO-12	3/8"	12.2	16.5	35	50
WO-16	1/2"	16.0	20.5	50	50
WO-20	3/4"	20.3	25.7	60	50
WO-25	1"	25.5	31.7	80	50
WO-32	1-1/4"	32.5	39.5	90	25
WO-38	1-1/2"	38.0	46.5	110	25
WO-51	2"	50.4	60.0	150	20
WO-64	2-1/2"	62.5	73.0	190	10
WO-75	3"	75.0	87.0	220	10
WO-100	4"	98.5	113.0	300	10


■ 產品構造：其內核由熱鍍鋅鋼帶繞製而成。獨特的真空擠出工藝使得軟管外部覆上一層耐油PVC而不影響導管的彎曲性。

■ 工作溫度：-25°C ~ 90°C

■ 燃燒等級：V0(UL94),GB8624 B2

■ 防護等級：IP68

■ 顏色：黑色、灰色。其他顏色可以根據需求而定。



### □ Type-WO

WO is oil-resistant jacket hot-dipped galvanized steel conduit for high-flex

□ Structure: Its core consists of thick hot-dipped galvanized steel external covered with a layer of oil-resistant PVC

□ Temperature Range: -25°C ~ 90°C

□ Flame-retardant: V0(UL94),GB8624 B2

□ Protection Degree:IP68

□ Standard Color:Black and gray. Other colors available upon request

□ Properties or Applications:Type-WO conduit with a liquidtight function, high oil resistance, high mechanical strength, suitable for general industrial use oil, cutting oil. Passed RoHS