

輕型防水金屬軟管 (WR型)

Lightweight Liquidtight Flexible Metal Conduit (TYPE WR)

SONGYAM



WR型軟管 具有防液體滲漏功能, 良好的彎曲性, 機械強度好, 可以在不同的工業環境中使用 (如電力, 冶金, 機械加工中心, 機器人) 等行業。

通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
WR-6	3/16"	6.0	9.2	25	100
WR-8	1/4"	7.8	12.2	35	100
WR-10	5/16"	10.2	14.2	40	50
WR-12	3/8"	12.0	16.2	50	50
WR-16	1/2"	15.6	20.2	65	50
WR-20	3/4"	19.7	24.2	80	50
WR-25	1"	25.2	30.5	100	50
WR-32	1-1/4"	32.2	39.0	130	25
WR-38	1-1/2"	38.0	46.3	152	25
WR-51	2"	50.4	60.0	200	20
WR-64	2-1/2"	62.5	73.3	250	10
WR-75	3"	75.0	87.0	300	10
WR-100	4"	98.5	113.0	390	10

- **產品構造:** 其內核由熱鍍鋅鋼帶繞製而成, 獨特的真空擠出工藝使得軟管外部覆上一層PVC而不影響導管的彎曲性。
- **工作溫度:** -25°C ~ 90°C
- **阻燃等級:** V0(UL94), GB8624 B2
- **防護等級:** IP68
- **顏色:** 黑色、灰色, 其他顏色可以根據需求而定



Type-WR

WR is liquidtight jacket hot-dipped galvanized steel conduit for high-flex

- Structure:** Its core consists of hot-dipped galvanized steel, external covered with a layer of PVC

- Temperature Range:** -25°C ~ 90°C

- Flame-retardant:** V0(UL94), GB8624 B2

- Protection Degree:** IP68

- Standard Color:** Black and gray. Other colors available upon request.

- Properties or Applications:** Type -WR conduit with liquidtight function, good flexibility, and good mechanical strength, can be in different industrial environments (such as electric power, metallurgy, machining centers, robots), etc.

Passed RoHS