

## 不銹鋼防水金屬軟管 (WS型)

Stainless Steel Liquidtight Flexible Metal Conduit (TYPE WS)


SONGYAM



WS型軟管 具有防液體滲漏功能，良好的耐腐蝕性，機械强度高，適用於高潮濕、高腐蝕的工作環境，如：化工、鋼鐵、冶煉、船舶等場所。  
通過RoHS測試

型號 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
WS-6	3/16"	5.9	9.0	20	100
WS-8	1/4"	7.8	12.0	25	100
WS-10	5/16"	10.0	14.0	30	100
WS-12	3/8"	12.4	16.8	35	50
WS-16	1/2"	15.4	20.0	50	50
WS-20	3/4"	20.0	24.5	60	50
WS-25	1"	25.0	31.2	80	50
WS-32	1-1/4"	32.0	39.0	90	25
WS-38	1-1/2"	38.0	46.3	110	25
WS-51	2"	51.0	59.7	150	20
WS-64	2-1/2"	62.5	73.0	190	10
WS-75	3"	75.0	87.0	220	10
WS-100	4"	98.0	113.0	300	10

- **產品構造：**其內核由不銹鋼帶繞製而成，獨特的真空擠出工藝使得軟管外部覆上一層PVC而不影響導管的彎曲性。
- **工作溫度：**-25℃ ~ 90℃
- **阻燃等級：**V0(UL94),GB8624 B2
- **防護等級：**IP68
- **顏色：**黑色、灰色，其他顏色可以根據需求而定



### Type-WS

WS is liquidtight jacket stainless steel conduit for high-flex

- Structure:** Its core consists of SUS304 stainless steel, external covered with a layer of PVC.

- Temperature Range:** -25°C ~ 90°C

- Flame-retardant:** V0(UL94),GB8624 B2

- Protection Degree:** IP68

- Standard Color:** Black and gray. Other colors available upon request.

- Properties or Applications:** Type -WS conduit with liquidtight function, with excellent corrosion resistance, high mechanical strength, suitable for high humidity, high corrosion work environment, such as chemical, steel, metallurgy, shipbuilding and other places.

Passed RoHS