

## ■ 重型防水金屬軟管 (WV型)

Heavyweight Liquidtight Flexible Metal Conduit (TYPE WV)


SONGYAM



WV型軟管 具有防液體滲漏功能，高彎曲性、機械強度高，可以在不同的工業環境中使用（如電力，機車，化工，冶金，機械加工中心，機器人）等行業。  
通過RoHS測試

型号 Type	規格尺寸 Trade size	最小內徑 Min. inner(mm)	最大外徑 Max. outer(mm)	彎曲半徑 Bending(mm)	包裝數量 Coil(m)
WV-6	3/16"	6.0	9.2	20	100
WV-8	1/4"	8.1	12.2	25	100
WV-10	5/16"	10.0	14.2	30	100
WV-12	3/8"	12.2	16.5	35	50
WV-16	1/2"	16.0	20.5	50	50
WV-20	3/4"	20.3	25.7	60	50
WV-25	1"	25.5	31.7	80	50
WV-32	1-1/4"	32.5	39.5	90	25
WV-38	1-1/2"	38.0	46.5	110	25
WV-51	2"	50.4	60.0	150	20
WV-64	2-1/2"	62.5	73.0	190	10
WV-75	3"	75.0	87.0	220	10
WV-100	4"	98.5	113.0	300	10

- **產品構造：** 其內核由加厚熱鍍鋅鋼帶繞製而成，獨特的真空擠出工藝使得軟管外部覆上一層PVC而不影響導管的彎曲性。
- **工作溫度：** -25°C ~ 90°C
- **阻燃等級：** V0(UL94),GB8624 B2
- **防護等級：** IP68
- **顏色：** 黑色、灰色，其他顏色可以根據需求而定



### Type-WV

WV is liquidtight jacket hot-dipped galvanized steel conduit for high-flex

- Structure:** Its core consists of thick hot-dipped galvanized steel, external covered with a layer of PVC

- Temperature Range:** -25°C ~ 90°C

- Flame-retardant:** V0(UL94),GB8624 B2

- Protection Degree:** IP68

- Standard Color:** Black and gray. Other colors available upon request.

- Properties or Applications:** Type -WV conduit with liquidtight function, good flexibility and good bending resistance, good mechanical strength, can be in different industrial environments (such as electric power, metallurgy, machining centers and robots, etc),  
Passed RoHS